

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF CLAIMS:

1-26 cancelled.

12. (new) A piezoelectric type lighter comprising a flame-generation device which comprises a mechanism for releasing a jet of gas and a piezoelectric mechanism for generating a spark, characterized in that the lighter comprises two actuators able to make a pivoting movement under the action of a force applied by a user between a first so-called resting position and a second so-called active position, at least one of said actuators, referred to as the first actuator, being adapted to move independently of the second actuator and to act on at least one of said mechanisms, referred to as the first mechanism, the lighter being adapted to generate a flame externally of the lighter when the two actuators have pivoted.

13. (new) A lighter according to claim 12, characterized in that the second actuator, when it is displaced under the action of a force applied by a user, is adapted to drive the first actuator through a pivoting movement along a given path, the two actuators being situated one behind the other on that path.

14.(new) A lighter according to claim 12, characterized in that the first actuator is adapted to act on one of the mechanisms, referred to as the first mechanism, and the second actuator is adapted to act on the second mechanism.

15.(new) A lighter according to claim 12, characterized in that at the same longitudinal end of the lighter, each actuator comprises a cap adapted to be subjected to a force applied by a user of the lighter and which is arranged such that the two caps are situated side by side.

16.(new) A lighter according to claim 15, characterized in that the cap of the second actuator, referred to as the second cap, comprises at least one portion which penetrates into a region of the cap of the first actuator, referred to as the first cap, such that a force applied by a user in that region drives the two caps through a pivoting movement.

17.(new) A lighter according to claim 16, characterized in that the penetrating portion of the second cap has a bearing surface which is not smooth.

18.(new) A lighter according to claim 15, characterized in that the two caps have bearing surfaces presented to a user which are arranged at different levels along the longitudinal direction of

the lighter, the bearing surface of the second cap being arranged at a level below than that of the bearing surface of the first cap.

19.(new) A lighter according to claim 12, characterized in that one of the two actuators, in its resting position, covers a region of the lighter in which a flame is generated externally of the lighter when both mechanisms are activated.

20.(new) A lighter according to claim 19, characterized in that the actuator covering the region of the lighter in which a flame is generated is the second actuator.

21.(new) A lighter according to claim 12, characterized in that the first actuator is adapted to act on both the mechanisms and to generate a flame, the second actuator, in its resting position, covering a region of the lighter in which the flame is generated, thus preventing the latter from propagating externally of the lighter when the second actuator has not pivoted.

22.(new) A lighter according to claim 12, characterized in that the first mechanism is the spark generation mechanism.